

PLUS 15-10-500 ES

Screw compressor with belt transmission,
complete with tank and dryer.

Lubricated screw compressor with belt transmission, ETMII electronic
controller. Soundproof cab made of hot-painted sheet metal, complete
with 500-litre tank and refrigerated dryer

*Image is for illustrative purposes only



TECHNICAL DATA

Product code	V83NQ92FNM801	
Lubrication	Lubricated	
Air-end	FS26	
Air receiver (l)	500	
Power	15	
Air outflow	l/min.	1850
	m3/min.	1,85
	c.f.m.	65
Max. pressure	bar	10
	p.s.i.	145
Nr. of stages	1	
Sound level (dB(A))	70	
Voltage / Frequency (Volt / Hz)	400/50	
Connection (G)	1"	
Controller	ETMII	
Type motor	Electric	
Energy efficiency	IE3	
Gross weight (kg)	452	
Net weight (kg)	412	
Packaging dimensions LxWxH (mm)	2070x800x1850	
Net Dimensions LxWxH (mm)	2000x680x1630	

*Sound pressure level measurement carried out at a distance of 7 metres.

FNA S.p.A. - Via Einaudi, 6 - 10070 Robassomero (TO) - Italy - www.finicompressors.com - info@fnacompressors.com