

MICRO SE 3.0-08

\*Image is for illustrative purposes only

Screw compressor with belt transmission, compact and silent.

Three-phase lubricated screw compressor with belt transmission with electromechanical control and direct starter. Soundproof cab in hot-dip galvanised sheet metal for maximum silence



TECHNICAL DATA

|                                 |               |      |
|---------------------------------|---------------|------|
| Product code                    | V51JS72FNM760 |      |
| Lubrication                     | Lubricated    |      |
| Air-end                         | FS14          |      |
| Power                           | 3             |      |
| Air outflow                     | l/min.        | 430  |
|                                 | m3/min.       | 0,43 |
|                                 | c.f.m.        | 15   |
| Max. pressure                   | bar           | 8    |
|                                 | p.s.i.        | 116  |
| Nr. of stages                   | 1             |      |
| Sound level (dB(A))             | 59            |      |
| Voltage / Frequency (Volt / Hz) | 400/50        |      |
| Connection (G)                  | 1/2"          |      |
| Controller                      | Login         |      |
| Type motor                      | Electric      |      |
| Energy efficiency               | IE3           |      |
| Gross weight (kg)               | 110           |      |
| Net weight (kg)                 | 99            |      |
| Packaging dimensions LxWxH (mm) | 720x670x970   |      |
| Net Dimensions LxWxH (mm)       | 580x480x760   |      |

\*Sound pressure level measurement carried out at a distance of 7 metres.