

MICRO SE 3.0-08-200 ES

*Image is for illustrative purposes only

Screw compressor with belt transmission, complete with tank and dryer.

Three-phase lubricated screw compressor with belt transmission with electromechanical control and direct starter. Sheet metal soundproof cab complete with 200-litre tank and refrigerated dryer



TECHNICAL DATA

Product code	V77JS72FNM801	
Lubrication	Lubricated	
Air-end	FS14	
Air receiver (l)	200	
Power	3	
Air outflow	l/min.	430
	m3/min.	0,43
	c.f.m.	15
Max. pressure	bar	8
	p.s.i.	116
Nr. of stages	1	
Sound level (dB(A))	59	
Voltage / Frequency (Volt / Hz)	400/50	
Connection (G)	1/2"	
Controller	Login	
Type motor	Electric	
Energy efficiency	IE3	
Gross weight (kg)	210	
Net weight (kg)	177	
Packaging dimensions LxWxH (mm)	1560x660x1430	
Net Dimensions LxWxH (mm)	1480x520x1280	

*Sound pressure level measurement carried out at a distance of 7 metres.

FNA S.p.A. - Via Einaudi, 6 - 10070 Robassomero (TO) - Italy - www.finicompressors.com - info@fnacompressors.com