

CUBE 5.5-10

Compact, direct drive transmission screw compressor.

Three-phase lubricated screw compressor with gearless coaxial transmission for efficiency and reliability. Particularly compact and easy to install and maintain



TECHNICAL DATA

|                                 |                 |      |
|---------------------------------|-----------------|------|
| Product code                    | V51PE92FNM443   |      |
| Lubrication                     | Lubricated      |      |
| Air-end                         | FS26            |      |
| Power                           | 5,5             |      |
| Air outflow                     | l/min.          | 705  |
|                                 | m3/min.         | 0,71 |
|                                 | c.f.m.          | 25   |
| Max. pressure                   | bar             | 10   |
|                                 | p.s.i.          | 145  |
| Nr. of stages                   | 1               |      |
| Sound level (dB(A))             | 68              |      |
| Voltage / Frequency (Volt / Hz) | 400/50          |      |
| Connection (G)                  | 1/2"            |      |
| Controller                      | ETMII           |      |
| Type motor                      | Electric        |      |
| Gross weight (kg)               | 111             |      |
| Net weight (kg)                 | 100             |      |
| Packaging dimensions LxWxH (mm) | 720 x 670 x 970 |      |
| Net Dimensions LxWxH (mm)       | 650 x 580 x 750 |      |

\*Sound pressure level measurement carried out at a distance of 7 metres.