

BK119-500F-7,5

Professional two-stage belt compressor, ideal for heavy and continuous use.

A two-stage three-phase belt compressor designed for intensive use by professionals, it is equipped with a 7.5 hp pumping unit with highly efficient operation cast iron cylinders with large manifolds for better cooling and robust metal belt covers protecting moving parts. The 500-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.

\*Image is for illustrative purposes only



TECHNICAL DATA

|                                 |               |      |
|---------------------------------|---------------|------|
| Product code                    | BRTN801FNM874 |      |
| Lubrication                     | Lubricated    |      |
| Compressor pump                 | BK119         |      |
| Air receiver (l)                | 500           |      |
| Power                           | Hp            | 7,5  |
|                                 | kW            | 5,5  |
| Max. pressure                   | bar           | 10   |
|                                 | p.s.i.        | 145  |
| Nr. of cylinders                | 2             |      |
| Air displacement                | l/min.        | 860  |
|                                 | c.f.m.        | 30,3 |
| R.P.M.                          | 1250          |      |
| Voltage / Frequency (Volt / Hz) | 400/50        |      |
| Type motor                      | Electric      |      |
| Gross weight                    | kg            | 235  |
|                                 | lb            | 518  |
| Packaging dimensions LxWxH (mm) | 2010x650x1330 |      |
| EAN code                        | 8017750193052 |      |