

MSR - TECHNICAL SPECIFICATION

MSR2 / MSR3 / MSR3P / MSR5

Models		Spindle speed	Tool holder	Max. drilling diameter												Stroke	Motor		Rapid feed	Thrust	Wt.
				1 spindle			2 spindles			3 spindles			4 spindles			Max.	Spindle	Feed			
				AL	FC	ST	AL	FC	ST	AL	FC	ST	AL	FC	ST						
		min-1	mm	mm			mm			mm			mm			mm	kW	kW	mm/s	N	kg
MSR2	-5120H	12 000	ER8 Capacity (0,5 - 5)	4	2,5	2,5	-	-	-	-	-	-	-	-	-	40	0,4 Servo Motor	0,1 Servo Motor	Max. 250	400	11
		10 000																			
		8 000																			
		5 000																			
MSR3	-2-6075(L)(B)	7 500		3	2	1	-	-	-	-	-	-	-	-	-						
	-2-6055(L)(B)	5 500		4	2,5	1,5	4	2,5	1,5	-	-	-	-	-	-						
	-2-6040(L)(B)	4 000		5,5	4	2	5	4	2	4	3,5	2	3,5	3	2		0,37 Servo Motor				
	-2-6030(L)(B)	3 000		7	5	3	6	5	3	5	4	3	4	3,5	3						
	-2-1330(L)(B)	3 000	ER20 Capacity (1 - 13)	7	5	3	6	5	3	5	4	3	4	3,5	3	95 (145)		0,4 Servo Motor	Max. 250	1 450	23 (26)
	-2-1318(L)(B)	1 800		9	7,5	5	7	5,5	5	6	5	4	5,5	4	3,5						
	-6-1325(L)(B)	2 500		7	5,5	3,5	5,5	4,5	3,5	4,5	3,5	3	4	3	2,5						
	-6-1318(L)(B)	1 800		7,5	6	5	6	5	4	5	4	3,5	5	3,5	3		0,25 Servo Motor				
	-6-1313(L)(B)	1 300		8	7	6	6,5	5,5	5	6	5	4	5,5	4,5	3,5						
	-6-1306(L)(B)	600		11,5	9	8	8,5	7	7	7	5,5	4,5	5,5	4,5	3,5						
MSR3P	-1375(L)(B)	0 - 7 500	ER20 Capacity (1 - 13)	8	7	6	7	6	4	5	4	3.0	4.0	3.0	2,5	95 (145)	1,8 Servo Motor	0,4 Servo Motor	Max. 250	1 450	24 (27)
	-1330(L)(B)	0 - 3 000		13	11,5	10	10	8	6	8	6	5.0	6.0	5.0	4.0						
MSR5	-2420 (B)	0 - 2 000	ER32 Capacity (9 - 20)	24	18	16	21	13	11	17	10	9	14	9	8	0 - 150	4,0 Servo Motor	0,75 Servo Motor	125	5 500	85
	-2412 (B)	0 - 1 200		24	22	20	23	16	14	22	13	12	18	11	10						