

Aluminium
M39

Steel (ST)
M30

Rigid construction

Fast approach
Fast return

Long stroke up to
150 mm

Var. Variable speed

Multi-spindle heads
attachable

Models		Spindle speed		Tapping capacity								Stroke			Servo Motor	Wt.
		Fast approach	Pitch feed	1 spindle		2 spindles		3 spindles		4 spindles		Full	Fast approach	Pitch feed		
				AL	ST	AL	ST	AL	ST	AL	ST				mm	mm
				min-1		mm		mm		mm		mm		mm	mm	mm
SSTR2	-H103H	Max. 4 000	Adjust. range 0 ~ 4 000	M3	M3	-	-	-	-	-	-	Max. 50	Max. 50	Max. 40	0.4 kW 220 V 3 phase Rated Current 2.6 A	10
SSTR3	-H108	Max. 3 370	Adjust. range 0 ~ 1 999	M10	M8	M8	M6	M6	M5	M6	M4	Max. 70	Max. 70	Max. 40	1.8 kW 220 V 1 or 3 phase	24
	-L108	Max. 1 600	Adjust. range 0 ~ 960	M12	M12	M10	M8	M8	M6	M8	M6				Rated Current 8 A	
				M12	M10	M8	M6	M6	M5	M6	M5					
SSTR5	-H316	Max. 2 200	Adjust. range 0 ~ 1 980	M14	M8	M10	M6	M8	M6	M8	M5	Max. 80	Max. 80	Max. 40	2.3 kW 220 V 1 or 3 phase	50
	-L316	Max. 875	Adjust. range 0 ~ 780	M12	M8	M8	M6	M8	M5	M6	M4				Rated Current 9.5 A	
				M18	M12	M12	M8	M10	M6	M10	M6					
SSTR6	-H630 (B)	Max. 1 000	Adjust. range 0 ~ 1 000	M39	M20	M27	M12	M20	M10	M16	M8	Max. 150	Max. 150	Max. 150	3.0 kW 220 V 1 or 3 phase	90 (92)
	-L630 (B)	Max. 600	Adjust. range 0 ~ 600	M33	M16	M22	M10	M16	M8	M12	M6				Rated Current 22.6 A	
				M39	M30	M39	M22	M30	M16	M27	M12				M22	